

**Important Information
RETAIN FOR YOUR RECORDS**

ACRYLIC CARE AND MAINTENANCE

We recommend that you clean your acrylic bathing product made of Delta® ProCrylic® or Acrylic with Innovex® Technology with non-abrasive soaps and cleaners such as:

- Dishwashing Detergent
- Lysol® Power Bathroom Cleaner
- CLR® Bath & Kitchen® Cleaner
- Formula 409® All-Purpose Cleaner
- Iron Out® Rust Stain Remover

Use a terry cloth towel, soft cloth, or sponge. Avoid using abrasive scrubbing pads, steel wool, or sponges.

NOTICE: When using drain cleaner or clog remover, rinse thoroughly with water.

NOTICE: Certain chemicals and cleaners may deteriorate acrylic surfaces, causing cracks and, potentially, property damage. Never use cleaning products that state on their label that they are not suitable for use on Acrylic, ABS, Polystyrene, or Plastic. We do not recommend using solvents (turpentine, lacquer thinner, mineral spirits, paint thinner, MEK, xylene, acetone, naphtha, etc.), Simple Green® All-Purpose Cleaner, Pine-Sol® Original, Scrubbing Bubbles® Cleaner, Tilex® Bathroom Cleaner, The Works® Tub & Shower Cleaner, Lysol® with Hydrogen Peroxide Multi-Purpose Cleaner, or Windex® Vinegar Multi-Surface Cleaner.



see what Delta can do™

www.deltafaucet.com
800-355-2721
consumercare@deltafaucet.com

*All trademarks are the property of their respective owners.

91201 Rev. B 09/18

**Important Sealant Information
READ PRIOR TO INSTALLATION**

SEALANT

NOTICE: Acrylic latex and silicone sealants are not recommended due to the potential of poor adhesion and shrinkage, which could lead to leaks. For best results, use an advanced sealant such as:

- DAP® 3.0™ Kitchen, Bath & Plumbing High Performance Sealant
- LOCTITE® PL Heavy Duty Sealant
- Red Devil® RD3000™ Advanced Kitchen & Bath Sealant
- ECO-BOND® Kitchen-Bath-Plumbing Adhesive and Sealant

APPLICATION TIPS

Use painter's tape to mask off the seam to help make cleaning up easier. Maintain a constant speed when applying the bead. Use a caulk tool or a plastic spoon to work the sealant into the joint. Wetting the tool with denatured alcohol will help create a smooth finish. Follow the directions on the back of the tube for cure time.

NOTICE: Certain chemicals and cleaners may deteriorate acrylic surfaces, causing cracks and, potentially, property damage. After application/installation, clean up the product surface and remove any excess sealant with denatured alcohol only. Do not use solvents (turpentine, lacquer thinner, mineral spirits, paint thinner, MEK, xylene, acetone, naphtha, etc.).

MODEL# _____

DATE OF INSTALLATION _____



see what Delta can do™

www.deltafaucet.com
800-355-2721
consumercare@deltafaucet.com

Label Size = 9 1/2" x 6"

MASCO CORPORATION PLUMBING PRODUCTS DIVISION		Do Not Scale, All Dimensions in Inches Fractional Tol ± 1/16" For reference only, not for reproduction purposes.		COLOR #1 Magenta	COLOR #2 Yellow	COLOR #3 Black	COLOR #4	COLOR #5 PMS 200
THIS DOCUMENT AND ALL THE DATA IT CONTAINS IS THE SOLE AND EXCLUSIVE PROPERTY OF DELTA FAUCET COMPANY, DIVISION OF MASCO CORPORATION OF INDIANA AND SHALL NOT BE DISCLOSED TO OTHERS WITHOUT THE EXPRESS CONSENT OF DELTA FAUCET COMPANY. COPYRIGHT ©2018 MASCO CORP. of INDIANA				COATING Gloss Aqueous	CREATE DATE 09-19-2018	SCALE 75%	PREPARED BY JAT	APPROVED BY JAT
MATERIAL 12pt C1S	JOINT METHOD N/A			PART DESCRIPTION Care Card			MODEL NUMBER 91201	REV. B PAGE 1 of 1