



▲ Designate proper finish suffix



see what Delta can do™

SHOWER HEAD

■ 6-Spray Setting Shower Head

FEATURES:

- Touch-Clean® Spray Holes

STANDARD SPECIFICATIONS:

- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa (75661▲ only)
- Max flow rate 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa (75661D▲ only)
- Shower head with 6 spray settings – pause is a non-positive shut-off
- Change spray settings with easy-turn lever
- Fits standard 1/2"-14 NPT pipe fitting
- Ball connector swivel angle is 32° (16° per side)
- 6 Spray settings include: Full Body Spray, Full Spray with Massage, Massaging Spray, Shampoo Rinsing Spray, Drenching Spray, and Pause

WARRANTY:

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense® - Applies to 75661▲ only