


Submitted Model No.: _____
Specific Features: _____



▲ Designate proper finish suffix



LAVATORY FAUCETS

Two Handle Deck Mount

STANDARD SPECIFICATIONS

- Maximum flow rate 1.20 gpm @ 60 psi, 4.54 L/min @ 414 kPa.
- Three hole mount
- 1/4 turn handle stops
- Lever handle control mechanism is a rotating cylinder type with stainless steel plate and 90°rotating, with replaceable non-metallic seats.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Indicates compliance to ICC / ANSI A117.1
- EPA WaterSense®
- Verified compliant with 0.25% weighted average Pb content regulations.



Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-L-B2510LF Rev. D

55 E. 111th Street, Indianapolis, Indiana 46280
 350 South Edgeware Road, St. Thomas, Ontario Canada N5P 4L1
 © 2016 Masco Corporation of Indiana